QTY ITEM# PART# PART TITLE RBW6510G05431-6F-1 WRENCH -1 3 McMaster#98381A502 OR EQUIV. STEEL DOWEL PIN 3/16" DIA. X 5/16" LG. 2 0.14 REF 3 PL **SECTION A-A** RBW6510G05431-6F WRENCH ASSEMBLY #2 NOTES: 1) MATERIAL: N/A 2) HEAT TREAT: N/A 3) FINISH: BLACK OXIDE PER MIL-C-13924 CLASS 1 THEN APPLY A THIN LAYER OF OIL / CPC PER MIL-PRF-16173 GRADE 3 CLASS 1 OR MIL-C-81309 TYPE III 19-797 **NEW ISSUE** KPT OR MIL-C-23411A OR MIL-PRF-81309 AND WIPE OFF EXCESS REV. DESCRIPTION BY ECN# 4) TOLERANCES: X.X = +/- 0.1" / +/- 1° X.XX = +/-0.01" / +/-0.5° DESIGN DART AEROSPACE LTD X.XXX = +/-0.005" / +/-0.1° **DRAWN** HAWKESBURY, ONTARIO, CANADA **KPT** X.XXXX = +/- 0.0005" / +/- 0.05°
PARALLELISM, ECCENTRICITY AND SYMMETRY ABOUT ALL CENTER LINES = +/-0.005" TOOL PART # CHECKED VM REV. A RBW6510G05431-6F 5) UNITS: INCHES UNLESS OTHERWISE NOTED MFG. APPR. SHEET 1 OF 2 6) IDENTIFICATION: N/A APPROVED SCALE 7) ASSEMBLE AS SHOWN WRENCH ASSEMBLY #2 8) APPLY RETAINING COMPOUND LOCTITE 620 OR EQUIVALENT ON MATING SURFACES
THEN PRESS FIT ITEM 2 FLUSH WITH SURFACE OF ITEM -1, AND REMOVE EXCESS
9) THE TOOL ASSY MUST BE PACKAGED WITH A DESICCANT BAG INTO A TIGHT FITTING SEALED PLASTIC BAG NTS DATE 2019-07-03 COPYRIGHT © 2019 BY DART AEROSPACE LTD

D

3

THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT

